

EMTB275 Mountain Bike– Vehicle Specifications

Electric System

Motor	Bafang M400, 48V/250W – Quick Release
Battery	Samsung, LI-ion 48V/14.5AH/250W – Lock System
Charger	100-240V, 50-60Hz
Display	King Meter J1 - LCD Display 5 Level Integrated
PAS	Torque Sensor

Performance Data

Security	GPS Tracking
Security	FoldyLock800 Bike Lock
Speed	25Km/hr
Range	Up to 100klms
Max Load	110kg
NW/GW	28g
Shipping Dimensions	1460*260*930

Frame	6061 Al Alloy / Headtube Flat Weld – 19”
Tyres	Maxxis 27.5 x 2.3 Sports”
Rim	Double Wall Al Alloy
Front Fork	RST /XCM Hydraulic Lockout Al Alloy Suspension
Spokes	13g Stainless Steel
Derailleur	Shimano Altus 7 Speed
Handle Bar	Promax Al Alloy
Stem	King Meter Al Alloy
Brake Level	TEKTRO Hydraulic Al Alloy, Power down when braking
Rear Brake	TEKTRO M350 Hydraulic Electric Cut Off
Front Brake	TEKTRO M350 Hydraulic Electric Cut Off
Chain	KMC- Rust Free
Chain Wheel	45T*175mm
Seat Post	Alloy Suspension Seat Post
Saddle	VELO Sports GEL / Selle Montegrappa Gel
Pedal	Al Alloy Reflective
Front/Rear Fenders	Polymer/PVE

