
Kimberley by Blade – Vehicle Specifications

Electric System

<i>Motor</i>	<i>Bafang Rear Drive, 36V/ 250W – Quick Release</i>
<i>Battery</i>	<i>Samsung Li-Ion 36V/13AH/250W</i>
<i>Charger</i>	<i>100-240V, 50-60Hz</i>
<i>Display</i>	<i>KD58C – Programmable LCD Display</i>
<i>PAS</i>	<i>PEDELEC, Bottom Bracket Sensor</i>

Performance Data

<i>Speed</i>	<i>25Km/hr</i>
<i>Range</i>	<i>55klms</i>
<i>Max Load</i>	<i>110kg</i>
<i>NW/GW</i>	<i>23kg</i>
<i>Shipping Dimensions</i>	<i>1520*300*820</i>

<i>Frame</i>	<i>6061 Al Alloy Adjustable Head tube Flat Weld</i>
<i>Tyres</i>	<i>Kenda Krusade 20*4" Fat Tyre</i>
<i>Rim</i>	<i>Double Wall Al Alloy</i>
<i>Front Fork</i>	<i>RST/XCM Guide-100mm Hydraulic Al Alloy Suspension</i>
<i>Spokes</i>	<i>13g Stainless Steel</i>
<i>Derailleur</i>	<i>Shimano 7 Speed</i>
<i>Handle Bar</i>	<i>Promax Al Alloy</i>
<i>Stem</i>	<i>Promax Adjustable Al Alloy</i>
<i>Rear Brake</i>	<i>TEKTRO E300 Mechanical Disc</i>
<i>Front Brake</i>	<i>TEKTRO E300 Mechanical Disc</i>
<i>Chain</i>	<i>KMC- Rust Free</i>
<i>Chain Wheel</i>	<i>38T*170mm</i>
<i>Seat Post</i>	<i>Suspension Alloy Seat Post</i>
<i>Saddle</i>	<i>Royal Gel Ebike saddle</i>
<i>Pedal</i>	<i>Al Alloy Reflective</i>
<i>Front/Rear Fenders</i>	<i>Gloss Polymer/PVE</i>